

While the water filled ballast bag concept is nothing new, several innovative features have been incorporated in Seaflex WaterLoad Test Weights to make the user's life easier. Filling is by 2½" full bore 'fire hose' terminating in quick release couplings compatible with standard hydrants. Seaflex 'J' Tube arrangement can be positioned anywhere over the hem of the bag *after* attachment to the crane's hook to prevent the risk of the fill hose being trapped between bags. The invert of all units of 15t and above are fitted with 3" bronze camlock coupling to accept a 3" discharge hose which empties a 35t unit in 22 minutes. Similar 2" camlock fittings on all units up to and including 10t ensure minimum time wasted after the test.

Handling the larger units has been greatly eased by delivering them in their own dedicated storage boxes which allows the bag to be hoisted straight out of the box for filling, and when emptied, lowered and flaked back down with minimal site handling. This reduces the manpower required, reduces site time and keeps the bags protected at all times.



UNIT		PACKED			FILLED		
Type	Kg	L	W	H	Kg	Diameter	Height
1-WLB	1,000	0.5	0.35	0.25	22	1.60	1.90
2-WLB	2,000	0.75	0.40	0.25	33	1.80	2.50
3-WLB	3,000	0.80	0.35	0.30	42	1.80	2.70
5LH-WLB	5,000	0.90	0.50	0.35	58	2.20	3.10
10-WLB	10,000	1.10	0.50	0.40	85	2.30	4.80
15-WLB	15,000	1.20	1.00	0.40	145	2.70	5.40
20-WLB	20,000	1.20	1.00	0.55	160	3.20	5.50
25-WLB	25,000	1.20	1.10	0.65	210	3.80	5.90
35-WLB	35,000	1.20	1.10	0.80	240	4.15	6.60



WATERLOAD TEST WEIGHT RENTAL

Seaflex hold large quantities of WaterLoad test weights at their head quarters in Cowes, UK and have established stock holding agencies throughout Europe, USA, Middle East, Far East, and Australia. For agent contact details please visit www.seaflex.co.uk

Individual bags can be hired by the day (subject to a minimum 2 day period), or for larger load tests with typically a greater hire period, lump sum hire charges are offered reflecting appreciable discounts.

Additional items are also available including 3:1 fill manifolds, calibrated water meters, compressed air and petrol driven water pumps, Fireman's hoses (75ft), certified shackles and calibrated load cells.